



## Shower door, recessed, 120 cm - sliding Cynia



Manufacturer	
Weight	32.99 kg
Product Code	KTC_012P
EAN	5908212028742
SKU	002014
IBB ID	12294

### Product specification

Manufacturer	DEANTE	Unit	pcs
EAN	5908212028742	Active cover layer	YES
Additional characteristics	cool-out	Frame height adjustment [mm]	200
Aerator size	M28	Aerator type	coin-slot
Ceramic cartridge size	35 mm	Adjustment range from [mm]	-30
Connection thread	m8	Flow class [l/min]	z - 4-9 l/min
Material	ZnAl	Installation method	possibility of installation with two fixed walls. possibility of installation with one fixed wall
Height [mm]	2000	Connection diameter	50
Double bearing upper rollers	YES	Glass finish	transparent
Reversible door	Ye	Silent closing	Yes
Possibility of installation without a shower tray	Yes		

Tempered glass has a harder surface and is more resistant to scratches, impacts and sudden temperature changes - in accordance with the European standard PN-EN. In addition, it is safe glass, (which is certified) by the Certificate from the Institute of Glass and Ceramics.

The glass in the cabins has been covered with the innovative Active Cover hydrophobic coating, which repels water molecules from the glass surface and thus significantly reduces the formation of scale. The coating is applied during the production of glass, which provides its long durability and reliability.

The covers hide the unsightly assembly elements, adding elegance to the cabins.

The use of dedicated agents means that the surfaces do not deteriorate and remain smooth for long, facilitating another cleaning. A specially selected composition removes the most common dirt extremely effectively. On the other hand, the preparations are delicate for a given type of surface (metal, granite, ceramics and others), without entering into chemical reactions with them. The preparations are biodegradable and thus

safe for the environment. With Deante cleaning products, keeping things in order will be very easy!

The profile system makes it possible to level the curvature of the walls and helps to adjust the cabin to the place of installation.