



Washbasin tap, contactless, with temperature control

- 230/6V Sense



Manufacturer	
Weight	1.91 kg
Product Code	BQR_F29V
EAN	5907650819714
SKU	003221
IBB ID	12512

Product specification

Manufacturer	DEANTE	Unit	pcs
EAN	5907650819714	Series	sense
Additional characteristics	cool-out	Acoustic group [dB]	I (x ≤ 20)
Frame height adjustment [mm]	200	Aerator size	m24
		Aerator type	movable, silicone
Ceramic cartridge size	35 mm	Adjustment range from [mm]	700
Connection thread	m8	Flow class [l/min]	z - 4-9 l/min
Installation thread	1/2"	Material	ZnAl
Mixer type	sensor	Installation method	standing
Range of tap spout [mm]	110	Connection diameter	50
Total height of the battery [mm]	146		

The sensor tap has a 3 mm stainless steel armored housing. It is equipped with a movable aerator, which is deeply embedded in the body. This solution provides additional protection against the destruction or damage of this element.

It is a new generation sensor that collects electricity in an impulse way, i.e. when opening and closing the water stream. This solution allows for comfortable use of the tap with minimal power consumption.

The tap is equipped with an aerator, thanks to which the water stream is perfectly aerated and soft. This solution improves the comfort of use, while limiting water consumption, which translates into lower utility bills. You are also contributing to taking care of our planet.

The movable aerator allows you to direct the stream of water and aerates it at the same time. This translates into less use of this valuable resource, while maintaining the comfort of using the mixer.

The silicone aerator adds air to the water stream, and at the same time gives the ability to easily remove lime sediment - just wipe its silicone edges with your finger.

The flow class with means that within a minute the tap flows between 4 and 9 liters of water. The stream is also comfortable to use, delicate and soft. This solution is ideal wherever you pay attention to ecological and economic responsibility - which also means your home!

The sensor is located right next to the aerator, so it is not flooded by water dripping from wet hands. It is a very precise device, resistant to external interference from its environment.

The product is made of the highest quality 304 stainless steel, in a brushed finish. The surface structure is extremely durable, resistant to scratches and cleaning agents.

Backflow valves guarantee the correct operation of the fittings, and in thermostatic taps they also prevent water mixing in the pipes.