



Facade silicone renovation paint ATLAS SALTA N white 10 l



Brand	ATLAS
Manufacturer	
Weight	15.00 kg
Product Code	BAN-SAH-000-110
EAN	5905400266061
SKU	003448
Advice IBB	
Application	For the renovation of old building facades and new renders
IBB ID	13288

Product specification

Manufacturer	ATLAS	Unit	pack
Brand	atlas	EAN	5905400266061
Coverage	thin-layer renders approx. 4.0 m ² /l, smooth plasters approx. 6.6 m ² /l	Relative air humidity during application and curing	< 80%
		Density of the finished product	ca 1.9 g/cm ³
pH	8		

Facade silicone renovation paint ATLAS SALTA N white 10 ltr

Most important features:

for the renovation of old building facades
 façade self-cleaning ability
 low absorptiveness
 no primer required

Product description:

ATLAS SALTA N paint is the highest quality product based on silicone resin, polymer dispersion, organic and inorganic pigments, modifiers and hydrophobic agents.

Main properties:

Self-cleaning ability – owing to the content of silicone resin and siloxane hydrophobic agents the coated surface cleans itself

during precipitation.

Low absorptiveness – great content of polymer binders and hydrophobing agents ensures high level of protection against draining water and moisture.

High vapour permeability – provides free transport of water vapour through the painted substrate.

Perfect applicability and spreading – the mix of thinners brings excellent workability, eliminates splashing during application with rollers, ensures complete filling of space between aggregate, even in case of thick texture (at first coating).

Highly flexible – paint does not peel off and crack, works well with the substrate and compensates façade thermal strains.

Early resistance to rain – optimum setting time ensures complete resistance to rain just after 2 hours since application.

Free arrangement - palette of 400 popular colours, in accordance to SAH Colour Scheme for Renders and Paints. Individual colours based on a sample available as well.

High coverage and colour fastness - thanks to the organic and inorganic pigments used (including titanium white) with increased UV resistance, provides an excellent and long-lasting effect in just one coat.

Application at reduced temperatures - with the addition of ATLAS ESKIMO, it is possible to use the paint at reduced temperatures (up to 0°C) and at increased humidity (up to approx. 80%).

Recommended for fresh renders - can be applied to fresh mineral renders as early as 5 days after application.