



Filling gypsum for tapeless jointing ATLAS STONER

5kg



Brand	ATLAS
Manufacturer	
Weight	5.00 kg
Product Code	AT-STONER-F-05
SKU	003462
Advice IBB	
Application	For levelling substrates, repairing cavities and cracks, filling in fissures
IBB ID	10379

Product specification

Manufacturer	ATLAS	Unit	pack
Brand	atlas	Colour	white
Coverage	approx. 0.5 kg per 1 meter of plasterboard joint	Norm	EN 13963:2005 + AC:2006
		Relative air humidity during application and curing	< 80%
Density of the finished product	ca 1.9 g/cm3	pH	8

Filling gypsum for tapeless jointing ATLAS STONER 5kg

Most important features

- high strength and hardness
- excellent application even at high temperatures
- easy to process - manual and mechanical sanding
- for levelling substrates, repairing cavities and cracks, filling in fissures
- easy application - very good ductility

Product description

Plasterboards jointing – no need for additional reinforcement in the form of tapes in the case of boards with pre-shaped edges
Repairs of wall and ceiling surfaces– recommended for gypsum substrates, for local repairs of gypsum plasters, top finishes or plasterboards.

Main properties

- Fibre reinforcement - fibres improve water retention, making the mortar easier to mix and distribute; once set, they reinforce and thicken the structure of the hardened gypsum, increasing its resistance to possible cracking.

- Plasticity - it is easy and very convenient to apply, both when inserting between plasterboards and when smoothing and final profiling the surface.
- Increased strength - provides a permanent, sufficiently strong and flexible joint between plasterboards
- Low shrinkage during setting - the lack of internal stresses arising in the gypsum layer ensures high stability of the resulting joint; the mass is stable, does not drag or swell.
- Long pot life when mixed with water - 60 minutes.