



Natural Pine Centre Pivot Roof Window FTP-V U3 02

FSC 55x98cm



Manufacturer	
Country of manufacture	Poland
Dimension	55cm x 98cm
Weight	23.00 kg
Product Code	FTP-V U3 02 FSC 55x98 Window
EAN	5900988720028
SKU	003684
Advice IBB	
Application	Centre pivot roof window with a V40P automatic air inlet
IBB ID	13541

Product specification

Manufacturer	FAKRO	Unit	pcs
EAN	5900988720028	Dimension	55cm x 98cm
Country of manufacture	Poland	Air inlet air flow	up to 49m ³ /h
Air inlet type	automatic v40p	Benefit 1	Security system FAKRO topSafe
Benefit 2	Handle at the bottom giving greater spread of daylight into the room	Benefit 3	Reliable sash guiding system
		Benefit 4	Easy to fit with universal bracket fix system
Hatch thickness [cm]	3.6	Benefit 5	Moisture-preventing unique drainage system
Insulation thickness [cm]	3	Ladder U-value [W/m ² K]	1.10
Acoustic insulation Rw	32 db	External colour	umbra grey ral 7022
maximum loading	160kg	External glass toughened	Yes
Finish	natural pine	Glazing	u3 - double glazed - energy-saving
Glazing unit	4h-16-4t	Glazing U-value [W/m ² K]	1.00

Inert gas filled panels	argon	Material	wood/aluminium
Maximum pitch	90°	Mechanism	manual
Minimum pitch	15°	Window U-value [W/m²K]	1.30

Natural Pine Centre Pivot Roof Window (FTP-V)

FAKRO offer four internal style finishes with an elegant handle at the bottom for ease of operation. Centre pivot roof windows can be made in natural pine, white acrylic, white polyurethane and white UPVC finishes - this is entirely up to you! All of these roof windows are manufactured with a V40P air inlet which by automatic adjustment of the flow channel size provides an optimum amount of air into the room.

- Manufactured in pine, vacuum impregnated and coated with acrylic lacquer
- Convenient way to use the window as the handle is located at the bottom of the sash. The handle is equipped with a two step micro-opening facility
- Easy cleaning of the outer pane and operating the awning blind with the use of blocking sash bolt when rotated through 180 degrees
- A wide range of accessories which include both internal and external blinds. This window also has the ability to install electrical controls
- Centre pivot windows come with a V40P automatic air inlet
- Can be used on roofs with pitches between 15-90°

FAKRO roof windows are not supplied with flashing kits unless otherwise stated

Specifications:

- FSC Certified
- BBA Approved (02/3944)
- Semi-automatic pressure ventilation V40P to prevent wind gusting
- topSafe - security and safety offering reinforced hinge and keep together with a steel slat to the lower part of the sash to achieve at least class III safety as per EN13049
- External aluminium colour reference RAL7022
- Natural wood frame
- Internal finish 2 layers of clear lacquer
- Bottom placed handle with 2 micro opening positions
- Glass construction 4HO-Tg14Ar-33.1T
- Acoustic rating 35Db (-1.-3)