



# Acrylic elastic caulk UNIVERSAL ATLAS 001 white 280ml



Brand	ATLAS
Manufacturer	
Weight	0.50 kg
Product Code	AT-EAU-0028
SKU	003688
Advice IBB	
Application	<b>For quick filling of gaps, joints, corners and cracks in walls and ceilings</b>
IBB ID	13545

## Product specification

Manufacturer	ATLAS	Unit	pcs
Brand	atlas	Colour	white 001
Relative air humidity during application and curing	< 80%	Density of the finished product	ca 1.9 g/cm3
		pH	8

Acrylic flexible caulk UNIVERSAL ATLAS 001 white 280ml

### The most important features:

- excellent grip
- easy application and profiling
- painting after just 30 minutes
- increased resistance to shrinkage and cracking
- white color

### Description:

For quick filling of gaps, joints, corners and cracks in walls and ceilings.

Types of substrates: concrete, plaster, gypsum, plaster, putty, wood, MDF, HDF, chipboard, ceramic, steel, PVC and similar types of plastics.

Sealing joints in drywall construction made of plasterboards, finishing strips, built-in wardrobes, window sills, stair structures, roller blinds, window and door frames, plinths, cornices, stucco, coffers, rosettes.

For use inside buildings, on horizontal and vertical surfaces.

### Main properties:

ATLAS ELASTIC UNIVERSAL ACRYL is a quick-drying, plastic-elastic acrylic sealant, available in white, with the possibility of quick coating with paint.

It has very good adhesion to many materials without primer, even when the substrate is damp.

The acrylic surface can be painted with typical interior paints.

Possibility of painting after a short time after application - approx. 30 minutes \* (for a joint width of 5 mm).

Minimized formation of cracks and scratches.

Low shrinkage.

It has high temperature resistance - from -25°C to + 80°C.

High level of whiteness.

Yield from one package: approx. 11 m, with a joint width of 5 mm (consumption: approx. 100 ml / 3.9 m). The values given are estimates and depend on losses and losses associated with processing.