



Self-levelling screed cement-based rapid-set ATLAS SMS 15 1-15mm 25kg



Brand	ATLAS
Manufacturer	
Country of manufacture	Poland
Weight	25.00 kg
Product Code	SMS-15-Z-F-25
EAN	5905400279306
SKU	7243
Advice IBB	
IBB ID	7243

Product specification

Manufacturer	ATLAS	Unit	plastic bag
Brand	atlas	EAN	5905400279306
Country of manufacture	Poland	Coverage	16.6 kg / 1 m ² / 10 mm of layer thickness
Relative air humidity during application and curing	< 80%	Density of the finished product	ca 1.9 g/cm ³
		pH	8

ATLAS SMS 15 - fast-setting, self-leveling compound (1-15 mm)

Description:

Levels surfaces within 1 - 15 mm thickness range - both when substrate has only local irregularities and when it is whole executed with slight slope.

Elevates floor level in the whole room – e.g. when necessary to equalize the level of two adjacent rooms.

The main characteristics:

- under tiles, panels, carpet flooring, parquet
- foot traffic just after 4 hours
- tiling after 24 hours
- high compressive and flexural strength
- low linear contraction

The main parameters:

consumption: 16.6 kg / 1 m² / 10 mm of layer thickness

compressive strength: ≥ 25.0 N/mm²

layer thickness: 1 ÷ 15 mm