



Self-levelling screed cement-based rapid-set ATLAS SMS 30 3-30mm 25kg



Brand	ATLAS
Manufacturer	
Country of manufacture	Poland
Weight	25.00 kg
Product Code	SMS-30-Z-F-25
EAN	5905400279283
SKU	7567
Advice IBB	
Application	It has excellent flowability - it allows you to obtain a horizontal and smooth surface
IBB ID	7567

Product specification

Manufacturer	ATLAS	Unit	plastic bag
Brand	atlas	EAN	5905400279283
Country of manufacture	Poland	Coverage	16.5 kg / 1 m ² / 10 mm of layer thickness
Relative air humidity during application and curing	< 80%	Density of the finished product	ca 1.9 g/cm ³
		pH	8

ATLAS SMS 30 - fast-setting, self-leveling screed (3-30 mm)

Description:

Levels surfaces within 3 - 30 mm thickness range - both when substrate has only local irregularities and when it is whole executed with slight slope.

Elevates floor level in the whole room – e.g. when necessary to equalize the level of two adjacent rooms.

The main characteristics:

under parquet, tiles, panels, carpet flooring

foot traffic just after 4 hours

for leveling floors during renovation

limited linear contraction

The main parameters:

consumption: 16.5 kg / 1 m² / 10 mm of layer thickness

compressive strength: ≥ 30.0 N/mm²

layer thickness: 3 ÷ 30 mm