



Leveling mortar ATLAS ZW 330 3-30mm 25kg



Brand	ATLAS
Manufacturer	
Country of manufacture	Poland
Weight	25.00 kg
Product Code	ZW-330-25
EAN	5905400185270
SKU	6034
Advice IBB	
IBB ID	6034

Product specification

Manufacturer	ATLAS	Unit	bag
Brand	atlas	EAN	5905400185270
Country of manufacture	Poland	Coverage	15.0 kg / 1 m ² / 10 mm of layer thickness
Relative air humidity during application and curing	< 80%	Density of the finished product	ca 1.9 g/cm ³
		pH	8

ATLAS ZW 330

Product description

- Substrates repairs indoors and outdoors – enables filling gaps and cavities as well as leveling other substrate irregularities.
- Execution of bonded screeds.
- Enables quick start of successive operations – in standard conditions tiling just after approx. 5 hours (for layers 5 mm thick).
- Reduces the consumption of adhesive mortars, plasters, screeds and floors.
- Plastic consistency – working parameters ensure easy application and filling gaps in the repaired surface.
- High mechanical strength – compressive strength min. 20.0 MPa, flexural strength min. 4.0 MPa.
- Reinforced with polypropylene fibres which:
 - reduce cracking resulting from shrinkage during the mortar setting,
 - enable application of thicker mortar layers on vertical surfaces, with no slip effect,
 - ensure uniform water distribution during drying.
- No shrinkage cracks.
- Wide range of layer thickness – from 3 up to 30 mm in a single operation – one may extend the layer thickness up to 60 mm after mixing the mortar with quartz sand (grain size up to 2 mm) in 1:4 weight ratio (quartz sand : dry mortar) - recommended when filling gaps and leveling horizontal surfaces.

