



Acrylic render Atlas SAH N15 dotted white 25kg



Brand	ATLAS
Manufacturer	
Country of manufacture	Poland
Weight	25.00 kg
Product Code	BTSAH-A-N15-N-2017-125
EAN	5905400357806
SKU	7717
Advice IBB	
Application	For façades exposed to dirt and difficult operation conditions
IBB ID	7717

Product specification

Manufacturer	ATLAS	Unit	bucket
Brand	atlas	Colour	white
EAN	5905400357806	Country of manufacture	Poland
Coverage	2,5 - 3,0 kg/m2	Relative air humidity during application and curing	< 80%
Density of the finished product	ca 1.9 g/cm3	Outdoor use	Yes
		Frost-resistant	Yes
pH	8	The temperature of the mass preparation, the substrate and the environment before the commencement of works, during the works and during the binding period	5 to 30 °C
Structure	dotted 1.5mm	Waterproof	Yes

Acrylic render ATLAS SAH N15

Most important features:

low water absorptiveness

resistant to soiling
very good bonding to substrates
easy texture forming
improved resistance to mechanical damage

Product description:

ATLAS ACRYLIC RENDER is a thin-coat render for application of finishing coats with decorative spotted texture.

For indoor and outdoor use.

Recommended as a finishing coat during installation of building insulation with the use of polystyrene or XPS boards.

For façades exposed to dirt and difficult operation conditions – works perfectly on commercial, public access buildings (schools, kindergartens, hospitals, etc.), outhouses.

Main properties:

Thin-coat render based on advanced acrylic resin – up-to-date polymer binder significantly enhances previous limitations of acrylic renders – low water vapour permeability and vulnerability to soiling.

Forms dense and very clear spotted texture 1.5 mm or 2.0 mm thick.

Render with aggregate 1.5 mm thick is also recommended for machine application with rendering units.

BIO PROTECTION – creates unfavorable conditions for fungi and algae growth due to low water absorption and acid-alkaline reaction.

ELASTICITY AND STRENGTH – formula providing improved elasticity and resistance to impacts; render compensates stress resulting from surface hits better, keeps consistent, does not chip off.

COLOUR DURABILITY – advanced technology provides colour durability resulting from the use of modern pigments, automatic system of dosing and permanently supervised process of manufacturing – render keeps its initial colour, is more resistant to bleaching and UV radiation.

ENVIRONMENTALLY FRIENDLY – render recipe was designed in accordance to the sustainable development aspects: maximally reduced amount of volatile organic compounds and use of natural fillers only.

RESISTANT TO CRACKING – improved resistance resulting from the presence of dispersed microfibers, which strengthen the render within its entire volume – render is protected against possible cracks caused by tension and alternate surface heating and cooling.

Main parameters:

400 colours – in accordance with SAH Colour Scheme for Renders and Paints

1 texture – spotted – N

Aggregate grain size: up to 1.5 mm – N-15