



Sealant colorless roofing rubber TYTAN PROFESSIONAL 310 ml



Brand	TYTAN PROFESSIONAL
Manufacturer	
Weight	0.40 kg
Product Code	DAT-DE-XX-031
EAN	5903518007613
SKU	000460
IBB ID	9566

Product specification

Manufacturer	SELENA	Unit	pcs
Brand	tytan professional	EAN	5903518007613

Plastic-elastic rubber mass intended for sealing and roofing repairs.

It has excellent adhesion to most construction substrates, both porous and non-porous, including bituminous substrates, e.g. concrete, plaster, sheet metal, plastics, roofing felt and asphalt masses, etc. It is also suitable for damp smooth surfaces. Thanks to the very high resistance to the influence of weather conditions and the flexibility of the joint, the sealing made guarantees a durable waterproof barrier for a long time. After curing, it can be painted with most paints.

Benefits

Highly flexible, durable

On damp substrates

Paintable

Resistant to UV and weather conditions

Good adhesion to a wide range of building materials

Application

Roof flashing and sealing flashing elements, chimneys, eaves, gutters and downpipes, roof window flashings and other roofing flashings

Sealing minor leaks in roofing made of roofing felt, tiles, corrugated and trapezoidal sheet

Filling grooves and joints during waterproofing of building walls, e.g. at the foundation-wall junction, grouting joints with a maximum movability of 10%

Creating joints and seals in boats and applications requiring resistance to constant exposure to water

Technical data

Composition:

high quality synthetic rubber

Skin formation time (ASTM D1640) [min]: 5-15

Processing time [min]: about 15 min

Curing rate (ASTM D1640) [mm/24h]: 0.5-1.0

Temperature resistance [°C]: from -20 to +90

Optimum application temperature [°C]: from -10 to +30

Substrate temperature [°C]: from +5 to +50