



Priming mass for renders ATLAS Cerplast 5kg



Brand	ATLAS
Manufacturer	
Country of manufacture	Poland
Weight	5.00 kg
Product Code	CP-00-05
EAN	5905400530018
SKU	8768
IBB ID	8768

Product specification

Manufacturer	ATLAS	Unit	bucket
Brand	atlas	EAN	5905400530018
Country of manufacture	Poland	Coverage	0,3 kg/1 m ²
Relative air humidity during application and curing	< 80%	Density of the finished product	ca 1.9 g/cm ³
		pH	8

ATLAS CERPLAST priming mass for renders

Most important features:

- ensures perfect bonding of renders
- reduces absorptiveness and strengthens substrates
- facilitates render application and texture forming
- unifies substrate colour
- available in several colours

Product description:

Primes substrates beneath ATLAS thin-coat renders – mineral, acrylic, acrylicsilicone and mosaic DEKO M.
 Improves bonding – strongly bonds to substrates and applied renders.
 Limits substrate absorptiveness – prevents excessive water transfer from freshly applied renders into substrates.
 Facilitates application of subsequent coat – rough surface reduces “slip” of the applied render.
 Forms temporary protective layer for a façade – protects non-rendered façade against weather conditions within half a year.

Main properties:

Contains aggregate – improves bonding owing to significant broadening of the effective surface between layers (forms rough surface).
 Protects substrates against adverse effects of the new coat – forms chemical barrier between substrate and render, limits their interaction – reduces colour penetration from substrates and occurrence of stains on the render surface.

High bonding – min. 1.0 MPa for concrete.

White priming mass – additionally, with particular ATLAS DEKO M and other thin-coat renders, available in three main colours: brown, clinker, graphite.

The priming mass can also be coloured according to SAH Colour Scheme by the tinting systems.