



Masonry mortar for silicate elements SILMUR M-15 grey 25kg



Brand	ATLAS
Manufacturer	
Weight	25.00 kg
Product Code	SILMUR-M15S-25
EAN	5905400110142
SKU	8831
Advice IBB	
IBB ID	8831

Product specification

Manufacturer	ATLAS	Unit	bag
Brand	atlas	Colour	grey
EAN	5905400110142	Relative air humidity during application and curing	< 80%
Density of the finished product	ca 1.9 g/cm3	pH	8

ATLAS SILMUR - masonry mortars for silicate elements

Description

Recommended for constructing walls of silicate elements (all versions), concrete and aerated concrete (SILMUR M-10, M-7.5 and M-5).

Used as a thin joint masonry mortar – recommended joint thickness between 2 and 10 mm (optimum thickness: 2-3 mm).

Used for surface floating and smoothing - with recommended coat thickness: 2-5 mm.

The main characteristics

- white or grey in colour
- for surface floating
- four classes of compressive strength
- may be used in reduced temperatures (only SILMUR M-15)

The main parameters

- layer thickness: 2 - 10 mm
- consumption: 4 kg/1 m² or wall 24 cm thick
- compressive strength: category M5, M7.5, M10, M15 (description on bags)