Polystyrene insulation render fixing plug LTX 10x120mm

Manufacturer	
Weight	**0.01 kg**
SKU	**2376**
Product Code	**LTX10120(200)**
IBB ID	**2376**

Product specification

Plastic connector for fixing polystyrene in all substrates according to ETAG 014, in ETICS, EWI systems

Basic parameters of the product:
Diameter [mm] 10
Material Polyethylene / Polyamide + GF
Fastener type Hammered
Body dimensions Lk x dk [mm] 10 x 120
Body material Polyethylene
Screw / bolt / pin / nail material Polyamide + GF

NEW IMPROVED DESIGN:
- anchorage: 30 and 50 mm
- Thanks to the new design of the expansion zone, the connector can be installed in all categories of substrates while maintaining high strength parameters
Glass fiber reinforced pin
- Provides high strength during assembly,
The construction of the pin head facilitates assembly, seals the connection pin - connector sleeve
Special connector flange - Greater rigidity of the pressure plate, secure clamping of the fixed material
Innovative design of the sleeve - A large number of "pockets" of glue on the pressure plate increases the adhesion of the adhesive mortar

Mounting type Surface, Substrates according to ETAG014:
A - ordinary concrete,
B - full ceramic / silicate brick,
C - perforated (perforated) bricks,
D - elements on lightweight aggregate (LAC),
E - cellular concrete (AAC)

Hole/drill diameter up to [mm] 10
Body flange diameter Dk [mm] 60
Mounting hole depth ho [mm] 40/60*