



Chipboard & woodscrew PZ yellow zinc plated KDH

5.0 x 50mm



Manufacturer	
Weight	1.00 kg
Product Code	KDH-50050(X5)
EAN	5907704418429
SKU	3246
Advice IBB	
IBB ID	3246

Product specification

Manufacturer	WKREȚ-MET	Unit	kg
EAN	5907704418429	Coating	yellow zinc-plated
Diameter [mm]	5		

Wood chipboard screw KDH-5050 5.0x50mm (1kg ca.230pcs)

Hardened screw KDH is made of zinc-plated low carbon steel coated with yellow or blue protective coating.

Usage:

- Screws for connecting wooden elements including solid wood
- For fastening wood-based elements
- For fastening PVC elements

Screws have counter-sunk head with PZ drive, partial thread and a special cutting point suitable for connections in wooden structures.

Features and advantages of screws:

- wax coating – reduced torque, faster and easier installation
- counter-sunk head – ensures flush fitting of the screw in the installed member
- PZ drive – ensures fast and reliable installation
- profile of thread – provides fast and reliable connection
- full thread – guarantees to maintain secure and reliable fastening while keeping also appropriate distance between the frame and the substrate.

Method of installation:

1. Before installation select adequate length of screws depending on thickness of elements to be fastened and minimum anchorage depth
2. The fastened wooden elements should be defect-free (no knots, cracks, colourations, rots, structure and shape defects, mechanical damages) as any defects reduce their strength

3. Screws should be installed using screw gun and bit suitable for PZ drive
4. Screws should be driven directly in wooden substrate without prior drilling