



Water pump Sumpflo Kit with 301 Pump, chamber, Mini HL alarm, Access Cover 600 x 600 mm



Manufacturer	
Weight	8.00 kg
Product Code	SUMPFLO/AC
SKU	5629
Advice IBB	
IBB ID	5629

Product specification

Manufacturer	WYKAMOL	Unit	set
--------------	---------	------	-----

SumpFlo

The Wykamol SumpFlo is especially designed for the removal of groundwater from Type C basement waterproofing cavity membrane systems.

The SumpFlo Kit comprises of a polythylene tank, OPTIONAL locking access cover, (pedestrian duty, not suitable for roadways) and a powerful submersible pump.

The system is very versatile, enabling the installer to located inlets to their specifications.

The system comes complete with a High Level Alarm (9V), which acts as a warning system to alert the end user if the water rises above the normal operating level within the tank.

The alarm is designed to activate via a separate float switch.

Available with both 301 and 303 pumps.

The SumpFlo 301 Pump has a flow rate of 168 Litres per minute and a maximum vertical output of 6.8 metres

The SumpFlo 303 Pump has a flow rate of 240 Litres per minute and a maximum vertical output of 12.5 metres

N.B. When choosing pump sizes, remember that pumps generally lose 1 metre of vertical output for every added bend in the pipework.

Kit contains:

- Pipe Work
- 1 x Mini High Level Alarm
- 1 x Sump Chamber
- 1 x 301 Pump
- 1 Metal Access Cover 600 x 600 mm

Easy to install

Odour tight locking access cover

Variable inlet positions

Integral non-return valve preventing back flow

Durable polythylene tank

Pre-moulded flotation points preventing movement below ground

Integral step for dual pump setup

Powerful submersible pump