



Drywall screw for metal KSGM 4.8x100mm 200pcs



Manufacturer	
Dimension	4.8x100mm
Weight	3.00 kg
Product Code	KSGM-48100
EAN	5907704419174
SKU	2335
Advice IBB	
Application	Screw for fixing plasterboards to steel profiles
IBB ID	2335

Product specification

Manufacturer	WKREŹ-MET	Unit	pack
EAN	5907704419174	Dimension	4.8x100mm
Norm	PN-EN 14566	Coating	phosphated
Diameter [mm]	4.8	Drive type	ph-2

KSGM - screw for fixing plasterboards to steel profiles

The screws for fixing plasterboards are made of carbon steel covered with a special phosphate coating. The screws have a flat countersunk head, which ensures proper recess in the fastened element, and a steel thread with a sharp tip, which ensures durable and secure fastening in the steel substrate (thickness up to 0.75 mm) and facilitates the start of assembly. The head of the screw has a recess type PH-2, which enables installation using bits with an anchoring depth limiter. KTGM assembly, screws on tape, requires the use of a screwdriver with a tape feeder. Installation: 1. Before installation, identify the substrate in which the screw will be installed and compare the loads that the screw will carry with the load capacities 2. Select the appropriate length of the screw, depending on the thickness of the plasterboard to be fastened 3. Keep the recommended distances from the edge of the substrate (at least 1.5 cm) and the axial distances between the screws (not more than 25 cm) 4. Fastening is done using a cordless screwdriver, a cordless screwdriver with a tape feeder with screws or a hand screwdriver, without prior drilling 5. The head of the screw should be slightly sunk into the plasterboard. A screw inserted incorrectly (too shallow, too deep or crooked) should be removed and fixed in another place.