



# Drywall screw gypsum to wood KSGD 4.8x120mm

## 200pcs



Manufacturer	
Dimension	4.8x120mm
Weight	3.00 kg
Product Code	KSGD-48120
EAN	5907704420187
SKU	2349
Advice IBB	
Application	Screw for fixing plasterboards to wooden substrates
IBB ID	2349

### Product specification

Manufacturer	WKREȚ-MET	Unit	pack
EAN	5907704420187	Dimension	4.8x120mm
Norm	PN-EN 14566	Coating	phosphated
Diameter [mm]	4.8	Drive type	ph-2

The screws for fixing plasterboards are made of carbon steel covered with a special phosphate coating. The screws have a flat countersunk head, which ensures proper recess in the fastened element, and a wood thread with a sharp tip, which ensures durable and secure fastening in the wooden substrate and facilitates the start of assembly. The head of the screw has a recess type PH-2, which enables installation using bits with an anchoring depth limiter.

Types of substrates to which the KGD/KSGD/KMGD screw can be installed:

- wooden substrate
- substrate made of wood-based materials

Assembly method:

1. Before installation, identify the substrate in which the screw will be installed and compare the loads that the screw will carry with the load capacities
2. Select the appropriate length of the screw, depending on the thickness of the plasterboard to be fastened
3. Keep the recommended distances from the edge of the substrate (at least 1.5 cm) and the axial distances between the screws (not more than 25 cm)
4. Fastening is carried out using a cordless screwdriver or a hand screwdriver, without prior drilling
5. The head of the screw should be slightly sunk into the plasterboard. A screw inserted incorrectly (too shallow, too deep or crooked) should be removed and fixed in another place.