



# Rapid adhesive for ceramic tiles PALACE Multi-Flex grey 20kg



Manufacturer	
Weight	20.00 kg
EAN	5014205002382
SKU	6842
Advice IBB	
Application	S1 rapid elastic adhesive for indoor and outdoor use, suitable for underfloor heating
IBB ID	6842

## Product specification

Manufacturer	PALACE CHEMICALS	Unit	bag
Colour	grey	EAN	5014205002382
Coverage	2.5 - 4.0 kg/sqm	Norm	BS EN 12004 Type C, Class 2FTE-S1

### PALACE Multi-Flex Tile Adhesive grey 20kg

MULTI-FLEX is a cement-based, highly polymer modified, thin-bed ceramic tile adhesive, recommended for fixing all types of ceramic and porcelain floor and wall tiles.

Install a wide selection of natural stone, mosaics, porcelain and vitrified tiles within interior & exterior locations.

MULTI-FLEX will fix tiles onto a wide range of suitably prepared substrates including tile backer boards and sub-floor heating systems as well as bonding to impermeable surfaces, such as existing tiles and power-floated concrete.

Plywood & timber floors should either be removed or securely fixed and over-laid with a suitable Tile Backer Board.

Conforms to: BS EN 12004 C2FT-S1

Rapid setting high early strength  
 Fixes vitrified & natural stone tiles  
 For fixing to heated sub-floors  
 High Early strength  
 For use on 15mm plywood overlay

### SURFACE PREPARATION

The substrate must be clean, firm and free of dust, dirt, oil, grease and loose flaking coatings. It must also be structurally sound and strong enough to support the expected traffic loading.

PALACE MULTI-FLEX can be applied to dry or damp surfaces however moisture sensitive materials must be dry and remain dry after fixing.

Worn or porous surfaces should be sealed with PALACE TILERS PRIMER diluted as 1 to 3 with water.

PALACE MULTI-FLEX can be applied to Tile Backer boards overlaid onto a suitably rigid structure, such as well-braced 15mm waterproof plywood screw fixed at 300mm centres to supporting battens. Applications over sub-floor heating should allow 28 days before switching the heat on. PALACE MULTI-FLEX is not recommended for application directly onto tongue and groove timber floorboards or floating plywood floors.

Do not apply onto bare, un-sealed gypsum plaster or anhydrite floor screed before first priming this type surface with two coats of PALACE TILERS PRIMER, the first diluted 1 to 1 and the second neat.