



## Adhesive mortar for elevation STONE MASTER ready mix frost resistant bucket 15 kg



Manufacturer

Weight

15.00 kg

Product Code

FROST RESISTANCE

EAN

5905674241511

SKU

8053

IBB ID

8053

### Product specification

Manufacturer

STONE MASTER

Unit

pack

EAN

5905674241511

Frost-proof, non-flammable adhesive, easy to use and stable on a vertical surface, suitable for use on decorative stone, and ceramic floor and wall tiles. It is a mixture of binders, mineral fillers and modifying additives, factory prepared in a dry form. When mixed with water, it forms a homogeneous adhesive mass for applying in a thin layer.

Use on a seasoned surface, free from dust, grease, lubricants and residual paint. Put dry mix in a container with clean, cold water (3.6 liters per 15 kg of dry mix) and stir until a homogeneous mass forms. Then, when applying to a surface, proceed in accordance with specific instructions given on the package label. The work should be carried out at a temperature of 5 ° - 25 ° C.

Workability after mixing with water: approx. 2 hours.

Bonding ability: 48 hours. Consumption - approx. 1.4 kg/m<sup>2</sup> at 1 mm thickness of layer.

The maximum thickness of the mortar layer: 5 mm.

Available in 15 kg buckets